



◆ストレート形

RoHS 指令対応品

呼 び		呼 び		各 部 の 寸 法								標準色	適合電線範囲		適合工具	一箱入数
規格	ビニル	規格	ナイロン	d ₂	B	φ d ₁	F ₁	l ₂	l	L ₁	板厚		撚線mm ²	AWG		
	AVF0.08-3		-	3.2	5.2	2.2	5.9	9.5	12.5	18.0	0.8	黄	0.08	28	DS05N DH-1B	1,000 (100×10)
	AVF0.08-V3.5		-	3.7	5.7		7.7		15.0	20.5						
UL	AVF0.3-2		-	2.2	5.2		5.9		12.5	18.0						
UL	AVF0.3-3		-	3.2												
	AVF0.3-V3.5		-		5.7	2.2	7.7	9.5			0.65	黄	0.1 0.3	26-22	*DS05N *DH-1B *AC-5N-D	1,000 (100×10)
	AVF0.3-L3.5		-	3.7			6.7		15.0	20.5						
UL	AVF0.3-3.5		-		6.6		7.7									
UL	AVF0.3-4		-	4.3												
UL	AVF0.5-2	APF0.5-2		2.2	5.2		5.9		12.5	18.0						
UL	AVF0.5-3	APF0.5-3		3.2												
	AVF0.5-V3.5	APF0.5-V3.5			5.7	2.2	7.7	9.5			0.5	黄	0.3 0.5	22-20	*DS05N *DH-1B *AC-5N-D	1,000 (100×10)
	AVF0.5-L3.5	APF0.5-L3.5		3.7			6.7		15.0	20.5						
UL	AVF0.5-3.5	APF0.5-3.5			6.6		7.7									
UL	AVF0.5-4	APF0.5-4		4.3												
UL	AVF0.5-5	APF0.5-5		5.3	8.0		7.0									
UL	AVF1.25-M3	APF1.25-M3			5.6		5.0		14.2	19.2						
UL	AVF1.25-3	APF1.25-3		3.2	6.0		4.4									
	AVF1.25-V3	APF1.25-V3			5.7		6.3		15.2	20.2						
UL	AVF1.25-L3	APF1.25-L3			5.9		6.5		15.6	20.6						
UL	AVF1.25-C3.5	APF1.25-C3.5			6.0		4.5		12.8	17.8						
UL	AVF1.25-S3.5	APF1.25-S3.5			5.7		6.3		13.5	18.5						
UL	AVF1.25-3.5	APF1.25-3.5		3.7	6.0	3.3	4.4	9.5	14.2	19.2	0.8	赤	0.5	20-16	*3号D *34号 *34S *DH-1B *AC-5N-D	500 (100×5)
UL	AVF1.25-V3.5	APF1.25-V3.5			5.7		6.3		15.2	20.2						
UL	AVF1.25-L3.5	APF1.25-L3.5			5.9		6.5		15.6	20.6						
UL	AVF1.25-A3.5	APF1.25-A3.5			6.4		6.5		15.4	20.4			1.65			
UL	AVF1.25-S4	APF1.25-S4			6.8		6.8		15.6	20.6						
UL	AVF1.25-4	APF1.25-4		4.3	7.0		6.5									
UL	AVF1.25-A4	APF1.25-A4			8.3		7.1		16.2	21.2						
UL	AVF1.25-5	APF1.25-5		5.3	8.0		7.0		16.8	21.8						
UL	AVF1.25-6	APF1.25-6		6.4	9.7		7.6		17.0	22.0						
UL	AVF2-3	APF2-3		3.2	5.5		4.4		14.2	19.2						
	AVF2-A3	APF2-A3			5.7		6.1									
UL	AVF2-S3.5	APF2-S3.5		3.7	6.5		6.5		15.7	20.7						
UL	AVF2-3.5	APF2-3.5			6.5		6.0		15.8	20.8			1.04	16-14	*4号D *34号 *34S *DH-1B *AC-5N-D	500 (100×5)
UL	AVF2-M4	APF2-M4			6.4	3.9	6.7	9.5	15.6	20.6	0.8	青	2.63			
UL	AVF2-S4	APF2-S4		4.3	6.6		8.0		15.8	20.8						
UL	AVF2-4	APF2-4			6.9		7.2		16.2	21.2						
UL	AVF2-A4	APF2-A4			8.3											
UL	AVF2-5	APF2-5		5.3	8.5		8.5		17.2	22.2						
UL	AVF2-6	APF2-6		6.4	11.0		9.5		20.2	25.2						400 (100×4)
UL	AVF3.5-4	APF3.5-4		4.3	8.0	4.9	7.5	14.0	17.8	26.5	1.0	黄	2.63 4.6	12		300 (100×3)
UL	AVF3.5-5	APF3.5-5		5.3												
UL	AVF5.5-M4	APF5.5-M4		4.3	7.1		7.9		19.5	27.2					*5号	
UL	AVF5.5-4	APF5.5-4			8.5	5.4	7.2	14.0	18.0	25.7	1.0	黄	2.63 6.64	12-10	*DH-1B *AC-5N-D	300 (100×3)
UL	AVF5.5-5	APF5.5-5		5.3	9.0		8.5		19.0	26.7						
UL	AVF5.5-6	APF5.5-6		6.4	12.5				23.5	31.2						
UL	AVF5.5-8	APF5.5-8		8.4	15.0		10.5		24.5	32.2						200 (100×2)

1. 各呼びの印は、UL登録品、CSA登録品です。

2. CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。

3. 上記寸法表にかぎらず特注品もご相談ください。

4. *印はUL適合工具です。