
銅線用裸圧着端子 **角先開形端子** 〈F形〉









RoHS指令対応品

		5 40 - 1 11									RoHS指令				ᄁᄭᄱ
	160	呼び	-			部 0						合電線筆		適合工具	一箱入数
規	格	50.00.0	d ₂	В	L	F	Е	φD	ϕd_1	T	単線mm	撚線mẩ	AWG	D0004	
		F0.08-3	3.2	5.2	12.5	5.9	4.0	2.3	0.45	0.8	_	0.08	28	DS031	1,000 (100×10)
		F0. 08-V3. 5	3.7	5.7	15.0	7.7								DH-1B	(100 × 10)
(<u>(i)</u>		F0. 3-2	2.2 3.2	5.2	12.5	5.9									
•		F0. 3-3	3.2			77					0.32	0.1		*DS031	
		F0. 3-V3. 5	0.7	5.7		7.7	4.0	2.3	8.0	0.65	5	5	26-24	*DH-1B	1,000 (100×10)
		F0. 3-L3. 5 F0. 3-3. 5	3.7		15.0	6.7					0.6	0.3		*AC-5N-D	(100 × 10)
(a)			4.3	6.6		7.7									
(E)	<u>@</u>	F0. 3-4 F0. 5-2	2.2												
(e)	(E)	F0. 5-2	3.2	5.2	12.5	5.9					0.5	0.0		*DS031	
W.	All I	F0. 5-3 F0. 5-V3. 5	0.2			7.7									
		F0. 5-V3. 5	3.7	5.7		6.7	4.0	2.3	1.2	0.5	0.5	0.2	24-20	*DS031 *DH-1B	1,000
®	(F0. 5-13. 5	٥./		15.0	0.7	4.0	2.3	1.2	0.0	0.8	0.5	24-20	*AC-5N-D	(100×10)
(h)	(F)	F0. 5-3. 5	4.3	6.6	10.0	7.7									
(4)	(B)	F0.5-4	5.3	8.0		7.0									
6	(F)	F1.25-M3	0.0	5.6		5.0									
(1)	(B)	F1.25-3		6.0	14.2	4.4			1.7	0.8	0.57	5		*DS031 *==12 *5N18 *DH-1B *AC-5N-D	1,000 (100×10)
F	WE	F1.25-V3	3.2	5.7	15.2	6.3		3.4							
((1)	F1.25-L3		5.9	15.6	6.5	4.5								
<u>©</u>		F1. 25-C3. 5	_	6.0	12.8	4.5									
<u>@</u>		F1.25-S3.5		5.7	13.5	6.3									
(4)	(1)	F 1. 25–3. 5		6.0	14.2	4.4									
<u>@</u>		F1. 25-V3. 5	3.7	5.7	15.2	6.3					5				
<u>@</u>	(1)	F1. 25-L3. 5		5.9	15.6						-				
<u>w</u>	⊕	F1. 25-A3. 5			15.4	6.5					1.44	1.65			
<u></u>	⊕	F1.25-S4		6.4	15.6	6.8									
<u>•</u>	⊕	F1. 25-4	4.3	7.0		6.5									
<u>•</u>	⊕	F1.25-A4		8.3	16.2	7.1									
<u>•</u>	®	F1.25-5	5.3	8.0	16.8	7.0									
<u>•</u>	(§)	F1.25-6	6.4	9.7	17.0	7.6									
(4)	⊕	F2-3	0.0	5.5	110	4.4									
		F2-A3	3.2		14.2	6.1									
(4)	(B)	F2-S3.5	3.7 4.3 5.3	5.7	15.7	6.5		4.2		0.8	1.14			* = = 12 *5N18 *214A *DH-1B	
(4)	⊕	F2-3.5		6.5	15.8	6.0	4.5		2.3						
(4)	(B)	F2-M4		6.4	15.6	6.7					(
(4)		F2-S4		6.6	15.8	8.0	4.0)				
(4)	⊕	F2-4		6.9	16.2	7.2					1.82	2.63		*AC-5N-D	
(4)		F2-A4		8.3										*REC-14A	
(4)		F2-5		8.5	17.2	8.5									
<u>(H)</u>		F2-6	6.4	11.0	20.2	9.5									500 (100×5)
(4)		F3. 5-4	4.3	8.0	17.8	7.5	5.3	5.0	3.0	1.0	1.82 { 2.4	2.63	12	*5N18, *214A *DH-1B, *REC-14A	500
<u>@</u>		F3. 5-5	5.3				0.0	0.0	0.0	1.0	2.4	4.6	14	*AC-5N-D	(100×5)
(4)		F5. 5-M4	4.3	7.1	19.5	7.9								*5N18	
	(B)	F5. 5-4		8.5	18.0	7.2					1.82	2.63		*214A	500
(4)	⊕	F5. 5-5	5.3	9.0	19.0	8.5	6.3	5.6	3.4	1.0	5	S	12-10	*DH-1B	(100×5)
	⊕	F5. 5-6	6.4	12.5	23.5	10.5					2.89	6.64		*AC-5N-D	
<u>(4)</u>	(B)	F5.5-8	8.4	15.0	24.5	10.0								*REC-14A	400 (100×4)

^{1.} 各呼びの印は、UL登録品、CSA登録品です。 2. CSA登録品としてご使用の際は、注文時にご指示ください。カートンがCSA品用となります。 3. 上記寸法表にかぎらず特注品もご相談ください。 4. *印はUL適合工具です。